

ΚΟΜΕΤ Α.Ε. Βιομηχανία Αυτοκολλήτων

PP Acrylic 28my LN AC 820LN

TECHNICAL DATA SHEET

DESCRIPTION:

High-grade water based low noise acrylic tape.

Carrier BOPP 28my film, with 22my adhesive for manual carton sealing packaging applications.

Low noise properties. Available also in red, yellow, blue and green.

APPLICATIONS:

- Manual carton sealing.
- Adhesion on uneven surfaces due to high amount of adhesive.
- Particularly suitable for all sorts of packaging applications.
- Suitable for cold and hot temperatures.

PROPERTIES:

- · Environmentally friendly and ecological adhesive.
- Moisture compatible after application.
- UV resistant adhesive.
- · Resistance to temperature changes.
- · Longevity of application

NOMINAL VALUES:

Backing

Biaxially Oriented Polypropylene (BOPP)

Adhesive

Acrylic (Water-based)

Tensile Strength MD

 $140 \pm 30 \, (N/mm^2)$

TM 5004 by Afera

Elongation at Break MD

 $140 \pm 30 (\%)$

TM 5004 by Afera

Adhesion to Steel

5.8 ± I (N/25mm)

TM 500l by Afera

Shear to Steel

Over I70 (h, 25mm x 25mm on stainless steel, 23°C)

TM 5012 by Afera

Rolling Ball Task

Under 3 (cm)

PSTC-6 (PSTC)

Film thickness

 $28 \pm I(mic)$

Film Colors Transparent

✓

Adhesive Color Transparent

Brown White

Red Yellow Blue Green