

## ΚΟΜΕΤ Α.Ε. Βιομηχανία Αυτοκολλήτων

Σωρού 12 | 144 52 | Μεταμόρφωση, Αττικής T 210 240 9796-9 F 210 240 9793 E info@komet-tapes.gr www.komet-tapes.gr

# PP Solvent 28my HT ST 608 TECHNICAL DATA SHEET

# DESCRIPTION:

Solvent based Natural rubber tape, with high tack adhesive. Carrier BOPP 28mic film suitable for manual and automatic carton sealing packaging applications.

#### **APPLICATIONS:**

- Manual carton sealing
- · Recommended for automatic carton sealing machine use
- Adhesion on uneven surfaces due to excellent power
- Suitable for all sorts of packaging applications.
- Refrigeration use suitable.
- Temperature resistance after application.
- Suitable for use on most types of recyclable cartons, due to special adhesive compound

#### **PROPERTIES:**

- Moisture compatible after application
- Resistant to temperature changes
- Longevity of application
- Excellent adhesive power

### NOMINAL VALUES:

Backing Biaxially Oriented Polypropylene (BOPP)

Adhesive Solvent-based, Natural Rubber

Tensile Strength MD I40 ± 30 (N/mm2) TM 5004 by Afera

**Elongation at Break MD I40 ± 30 (%)** TM 5004 by Afera

Adhesion to Steel 5.5 ± I (N/25mm) TM 500I by Afera

Shear to Steel Over 300 (h, 25mm x 25mm on stainless steel, 23°C) TM 5012 by Afera

Rolling Ball Task Under 3 (cm) PSTC-6 (PSTC)

Film thickness 28 ± I(mic)

Film Colors

Transparent 💋

Transparent 🛛

Adhesive Color

Brown